Quality for all safety

GUARANTEE
10 YEARS
SMOKE ALARM & BATTERY

3 VOLT PHOTO ELECTRIC (OPTICAL) SMOKE ALARM ASD-10Q

ASD-10Q **Optical smoke alarm incl. 3V Lithium battery**

Photo-electric detection, made in Europe
Storage temperature: 0 ° to 30 ° C, max. 55 ° C for up to 14 days
Operating temperature: 0 ° to 55 ° C. Operating humidity: <93% RH at 40°C
Power: 3V fixed Lithium battery, CR14505 AA, battery not replaceable
Standby current: <8uA Alarm current: <60mA
End of battery life indication 30 days
Battery operates at least 10 years under normal use
Sound alarm level: ≥85 dB at 3 metres, horn frequency: 3.1-3.4kHz
Hush time: 10±1 min **By pressing the test button for 1 sec., single LED flashes every 10 sec.**
Long Term Drift feature - sensitivity compensation **This mechanism automatically adjusts the smoke alarm's sensitivity to dust during operation.**
Optimized activation procedure - magnetic
The 10-second self-test feature includes: **Battery status, smoke chamber pollution and smoke sensor function** **Contamination indication: triple sound signal every 40 sec.** **Battery fault indication: single sound every 40 sec.**
Standby mode indication : single LED flashes every 320 sec.
Certification: **KRIWAN 1772-CPR-140007, EN-14604:2005/AC2008, vfdb 14-01, CE, DoP No: 10Q14,** **Federatie Veilig Nederland, Q-mark**
Dimension: Ø 80 mm., H. 48 mm - weight: 90 gram - colour: white - IP30
Easy installation: mounting material (screws and dowels) and BST adhesive base included **Only attach the smoke detector with the supplied adhesive strip or mounting material**
Packing: per piece in gift box 85 x 51 x 85 mm with Euro loch, **72 pieces outer carton (3 x 24 pieces inner carton)**
EAN-code: 8 713686 00 2306
Factory guarantee: 10 year smoke alarm and battery if properly maintained according to the user manual and activation within 14 months from production date.
Lifetime smoke alarm: 10 years