

### 3 VOLT PHOTO ELECTRIC (OPTICAL) SMOKE ALARM ASD-5



**ASD-5**                      Optical smoke alarm, incl. 2 x 1,5 V AAA alkaline batteries

**Photo-electric detection, manufactured in Europe**

**Power: 3V – 2 x 1.5V AAA LR03 batteries, replaceable**

**Usage: continuous <8µA, in alarm <70 mA**

**Batteries operate under normal conditions at least 5 years**

**End of battery life indication 30 days**

**Loud pulsating alarm ≥85 dB at 3 metres, horn frequency: 3.1-3.4kHz**

**Equipped with test button and hush / silent mode 10 ± 1 min.**

**During HUSH mode LED flashes every 10 seconds**

**Long Term Drift feature - sensitivity compensation**

**This mechanism automatically adjusts the smoke alarm's sensitivity to dust during operation.**

**The 10-second self-test feature includes:**

**Battery status, smoke chamber pollution and smoke sensor function**

**Contamination indication: triple sound signal every 40 sec.**

**Battery fault indication: single sound every 40 sec.**

**Certification: AFNOR 0333-CPR-292126, EN-14604:2005/AC:2008, CE, DoP No: 0523,**

**use according to DIN 14676**

**Certified for use in camper and caravan**

**Dimension: Ø 80 mm., H. 48 mm - Weight: 80 gram - Colour: white - IP30**

**Montage: delivered with mounting material (screws and dowels) and BST double-sided adhesive strip**

**Only attach the smoke detector with the supplied adhesive strip or mounting material**

**Packing: per piece in gift box with Euro loch, 72 pieces outer carton**

**EAN-code: 8 713686 00 2436**

**Factory guarantee: 5 year smoke alarm and batteries if properly maintained according to the user manual**

**Lifetime smoke alarm: 10 years**