

3 VOLT PHOTO ELECTRIC (OPTICAL) SMOKE ALARM ASD-5



ASD-5 Optical smoke alarm, incl. 2 x 1,5 V AAA alkaline batteries

Photo-electric detection, manufactured in Europe
Power: 3V – 2 x 1.5V AAA LR03 batteries, replaceable
Usage: continuous <8µA, in alarm <70 mA
Batteries operate under normal conditions at least 5 years
End of battery life indication 30 days
Loud pulsating alarm ≥85 dB at 3 metres, horn frequency: 3.1-3.4kHz
Equipped with test button and hush / silent mode 10 ± 1 min.
During HUSH mode LED flashes every 10 seconds
Long Term Drift feature - sensitivity compensation
This mechanism automatically adjusts the smoke alarm's sensitivity to dust during operation.
The 10-second self-test feature includes:
Battery status, smoke chamber pollution and smoke sensor function
Contamination indication: triple sound signal every 40 sec.
Battery fault indication: single sound every 40 sec.
Certification: AFNOR 0333-CPR-292126, EN-14604:2005/AC:2008, CE, DoP No: 0523, use according to DIN 14676
Certified for use in camper and caravan
Dimension: Ø 80 mm., H. 48 mm - Weight: 80 gram - Colour: white - IP30
Montage: delivered with mounting material (screws and dowels) and BST double-sided adhesive strip
Only attach the smoke detector with the supplied adhesive strip or mounting material
Packing: per piece in gift box with Euro lock, 72 pieces outer carton
EAN-code: 8 713686 00 2436
Factory guarantee: 5 year smoke alarm and batteries if properly maintained according to the user manual
Lifetime smoke alarm: 10 years