

ASD-RRC: REMOTE CONTROL FOR ASD-10QR WIRELESS SMOKE ALARMS



ASD-RRC

Remote control for ASD-10QR wireless smoke alarms

Using-friendly housing with mounting hole
Single Test-Button for all modes
Remote testing of Smoke Alarm ASD-10QR
Remote Hush function (reduced sensitivity) for ± 10 minutes
Alarm mode reset for nuisance alarm for ± 10 minutes
ON mode indication by LED if pushing the Test button
LOW Battery indicated by LED (< less than 10% of capacity)
Replaceable Battery CR2032

Specifications

<p>Standby current consumption ≤ 2,2 µA Transmit current consumption ≤ 17 mA RF Frequentation 868 MHz RF Power -6 dBm max RF Range 3-10 meters free field Battery life: 3 year normal condition</p>	<p>Battery type: lithium batterij 3V CR2032 Hush time ± 10 min. Temperature: 0-55 ° C Humidity <93% RV bij 40 ° C Dimensions 72 x 39 x 15 mm Colour: white/blue</p>
<p>Packing: Gift box Guarantee: 3 year</p>	<p>Certification: RED / CE EAN-code: 8713686002399</p>

Light signals

LED	Function
No light	Standby function
Frequent flashes	Transmit function
Flashes every 3 seconds	Low battery- Replace the battery