

3 VOLT CARBON MONOXIDE DETECTOR CO-828



CO-828 Carbon monoxide detector 10 years incl. 2 x 1.5 AA batteries

Electrochemical detection
Power supply: 3V, incl. 2 x 1.5V AA alkaline batteries
Lifespan of supplied batteries: ± 3 years, replaceable
Operation ambient condition: Temperature: -10° C to + 45° C Humidity: 25-95% relative humidity (non-condensing)
Storage/transport ambient condition: Temperature: -20° C to + 50° C Humidity: 25-95% relative humidity (non-condensing)
IP rating: IP20
Measuring range: max. 40 m² within 1 room
Equipped with test/silence button Silence alarm for 10 minutes: press the test/silence button Silence low battery notification for 9 hours: press test/silence button
Signals in case of alarm Audible notification: loudness at alarm: >85dB at 3 meters distance Visual notification: red LED flashes continuously
48 hour alarm memory
Signal at end of life
Certification: EN 50291-1:2018, CE
Easy installation, supplied incl. screws/plugs
Dimensions: 120 x 80 x 37 mm Weight: 102 gram Color: off-white
Packing: per piece in carton gift box 135 x 50 x 90 mm with euroloch, 40 pieces per outer carton
User manual: NL, FR, DE and EN in packaging
CO detector lifespan: 10 years
Warranty: 3 years, excl. batteries
EAN-code: 8 713 6860 04645