

230V SMOKE ALARM WIRELESS INTERCONNECTABLE FIT-230RF & FIT-230RFL



WIRELESS INTERCONNECTABLE:

- FIT-230RF** 230 VOLT OPTICAL SMOKE ALARM incl. Back-up 9V battery, ca. 2 year
- FIT-230RFL** 230 VOLT OPTICAL SMOKE ALARM incl. Back-up 9V lithium battery, ca. 10 year

Wireless connectable with FIT-230RF(L), FITH-230RF(L) and FIT-10YRF up to 40 pieces
RF distance minimum 80 meters in open space
Professional RF frequency: 868.52 MHz
If one smoke alarm goes into alarm, the interconnected alarms will also go into alarm
Self-learning coupling system, more than 1000 combinations possible
Photo-electric detection
Power: 220-240 Vac, 50-60 Hz
Back-up battery: 9V Alkaline battery (ca. 2 year) or 9V Lithium battery (ca. 10-year) replaceable
Installation without battery impossible
End of battery life indication for 30 days on all connected smoke and heat alarms
The initiator produces a different sound pattern
Provided with test button and HUSH feature
Loud pulsating alarm (85 dB at 3 meters)
Dimension: Ø 12 cm., H 5 cm., inclusive mounting plate
Weight: 208 grams
Colour: off-white
IP40
Guarantee: 5 years (battery excluded)
Certification: BSI 2797-CPR-638573, KM638574, EN14604:2005/AC:2008, CE, DoP No: 230RF20
Provided with back-up battery and mounting material
Packing: full colour giftbox per piece with Euro loch, 48 pieces outer carton, 12 pieces inner carton
EAN-code FIT-230RF: 8 713686 000494
EAN-code FIT-230RFL: 8 713686 000487