Quality for all safety

230-VOLT OPTICAL SMOKE DETECTOR FIT-BLACK23010



Product description

Mains-powered smoke detector, featuring photoelectric detection and a replaceable 9 V lithium backup battery (approx. 10-year lifespan).

Key features

- Wired interconnection possible for up to 40 units, including:
  - **FIT-230(10)** smoke detectors and/or
  - **FITH-230(10)** heat detectors
- Replaceable lithium backup battery
- Test button and loud, pulsating 85 dB alarm (at 3 m)
- Silence (HUSH) function for 10 minutes
- Smoke detector service life: 10 years

Technical specifications

Model	FIT-BLACK23010
Detection technology	Photoelectric
Power supply	220 to 240 VAC, 50 to 60 Hz
Backup battery	9 V lithium battery, approx. 10-year lifespan; replaceable
Alarm volume	885 dB, pulsed, at 3 m
Dimensions	Ø 12 cm × 5 cm height, including base plate
Weight	168 g
Color	Black
Degree of protection	IP40
End-of-Battery-Life Indication	For 30 days

Standards and certification

BSI 2797-CPR-796170 · EN 14604:2005/AC:2008 · CE · DoP No. 23023. Complies with NEN2555

Delivery and packaging

Delivery	Smoke detector with base plate, backup battery, and mounting hardware included.
Packaging	Individually packaged in a cardboard gift box measuring 123 x 61 x 128 mm, featuring a Euro-slot. 48 units per master carton; 4 boxes of 12 units each.
Warranty	**5-year** on the smoke detector (batteries excluded)
EAN code	**8 713686 000340**