

**230V HEAT ALARM WIRELESS INTERCONNECTABLE FITH-230RF & FITH-230RFL**



**FITH-230RF** 230 VOLT HEAT ALARM incl. Back-up 9V battery, ca. 1 year  
**FITH-230RFL** 230 VOLT HEAT ALARM incl. Back-up 9V lithium battery, ca. 10 year

Wireless connectable with FITH-230RF(L), FIT-230RF(L) and FIT-10YRF up to 40 pieces
RF distance minimum 80 meters in open space
Professional RF frequency: 868.52 MHz
If one smoke alarm goes into alarm, the interconnected alarms will also go into alarm
Self-learning coupling system, more than 1000 combinations possible
Detects fire by a vast temperature of approximately 60°C
Power: 220-240 Vac, 50-60 Hz
Back-up battery: 9V Alkaline battery (ca. 1 year) or 9V Lithium battery (ca. 10-year) replaceable
Installation without battery impossible
Back-up battery interchangeable
End of battery life indication for 30 days on all connected smoke and heat alarms
The initiator produces a different sound pattern
Provided with test/hush button
Loud pulsating alarm (85 dB) at 3 meters
Dimension: Ø 12,3 cm., H 6,6 cm., inclusive mounting plate
Weight: 156 gram excl. battery
Colour: off-white
IP40
Guarantee: 5 years (battery excluded)
Lifetime smoke alarm: 10 years
Certification: CE
Provided with back-up battery and mounting material
Packing: full colour giftbox per piece with Euro loch, 48 pieces outer carton, 12 pieces inner carton
EAN-code FITH-230RF: 8 713686 000449
EAN-code FITH-230RFL: 8 713686 000463