

MHUB ESSENTIAL – WORKS WITH FITO ASD-10QR & AHD-10QR



MHub Essential: full control over your Fito detectors and LiviSense sensors

Compatible with: -Google assistant en LiviSense app, te downloaden via Apple App-store of Google Play store	
Power supply: • 5 VDC, 1A • USB-C type connector	General: • Product size: 64 mm x 64 mm x 38 mm • Weight: 48 grams • Color: white
Operating temperature: -20 °C to 45 °C	
IP20: for indoor use	
Internet connection: • Wi-Fi Security Level: WEP, WPA, WPA2 (Personal) • Unobstructed wireless range in free field: >300m • Frequency: 2400-2495 MHz • Max. transmission power: 20 dBm	
Wireless connectivity: • Setup through Bluetooth LE V4.2 • Unobstructed wireless range in free field: >10m • Frequency: 2400-2483.5MHz • Max. transmission power: 9 dBm	
Communications: • Protocol: proprietary wireless protocol • Unobstructed wireless range in free field: >300m • Frequency: 868.65 MHz and 869.675 MHz • Max. transmission power: 14 dBm • AES-128	
Adheres to cyber security standards: • ETSI EN 303 645 V2.1.1 (2020-06) • OTA, encrypted flash, secure boot, e-fuses, TLS	
Contents of the package: delivered incl. wall bracket, USB power strip, USB-A to USB-C cable	
Packaging: individually in cardboard box with sleeve with Euroloch	
Certifications : CE, RoHS, ETSI EN 303 645 V2.1.1 (2020-06), OTA	
Guarantee: 5 years	
EAN code: 8 713686 006601	