

WIRELESS RELAY FIRE ALARM NETWORK QR-NA 12V



QR-NA 12V wirelessly connectable smoke alarm relay

Compatible with ASD-10QR and most alarm control panels	
Connection to the control panel through a dry contact NO/NC	
Creates a wireless network with up to 48 smoke detectors	
One button operation for all modes	
Self-recovery function	
LED-indication	
Possibility to amplify the signal by using an external antenna	
Made in Europe	
Input voltage:	
QR-NA 12 Volt:	9V until 15V
RF Specifications:	
RF Frequency:	868,100 (<1% duty cycle)
RF power:	+14 dBm max.
RF range:	Up to 100 m. of open space
RF range with external antenna:	Up to 300 m. of open space
NO/NC specifications:	
Contact with active load:	1A/30VDC; 0.5A/125VAC
Max. switching power:	30W (1A/30VDC), 62.5VA (0.3A/125VAC)
Max. switching voltage:	110VDC
Max. switching current:	1A DC
In accordance with RoHS	
Operating temperature:	0°C tot + 55°C
Dimension:	L 115 mm, W 87 mm, H 27 mm
Weight:	76 grams
Lifetime:	up to 10 years
Guarantee:	5 years
EAN-code QR-NA 12V:	8713686002511