

3V CARBON MONOXIDE DETECTOR (CO-detector) R200C-1



R200C-1 CARBON MONOXIDE DETECTOR 10 YEARS INCL. 3V LITHIUM BATTERY AUTONOMOUS

Electrochemical detection
Power: sealed long life 3V lithium battery, not interchangeable
Maintenance-free operation, no battery replacement necessary
Operation Ambient Condition
Temperature: -10 - + 40° C
Humidity: 25-95% relative humidity (non-condensing)
Storage/Transport Ambient Condition
Temperature: -15 - + 45° C
Humidity: 25-95% relative humidity (non-condensing)
Degree of protection IP44 > Suitable for bathroom conditions
The entire device cover is its TEST / SILENCE button
Hush alarm for 10 minutes: press the test button for 3 seconds
Hush error message for 9 hours: press the test button for 3 seconds
Audible: >85 dB @ 3 meters distance
Visual red 'ALARM' text for the deaf and hearing-impaired
48-hour alarm memory
End of life signal
Automatic dimming of the green 'Power' light in low ambient light
Tamper-proof (optional)
Certification :
EN 62368-1:2020 +A11:2020, EN CEI 63000:2018, EN 50270:2015, EN 50291, NF, Kitemark, B-mark
Suitable for use in domestic premises (including static caravan holiday homes), (motor) caravans and boats
Easy installation, supplied with screws/plugs
Dimensions: 95 x 95 x 25 mm Weight: 120 gram Color: off-white
Packaging: 120 x 35 x 160 mm cardboard gift box with Euroloch, 40 pieces per outer box
User manual in packaging: EN, DE, NL, FR, ES, IT, PT and SE
Warranty and product life: 10 years
EAN-code: 3 603940 006476