



## V-COM LED DIMMER

Art.nr.: MKP100.EU Program: Varilight LED Dimmers Category: V-Com



Mounting: built-in (clamp and / or screw) Diameter including matrix: 71x78x42 mm Product weight: 85 grams Installation depth: 26 mm Suitable for existing flush-mounted boxes

**Operating voltage:** 220 / 250V AC

Maximum load: 100W (max. 10 lamps) Maximum use: 0.4 A Connection diameter: 3.2 mm Connection: 3 x 1.5 mm<sup>2</sup>

## **Intended applications:**

For indoor use only. Commercial and household lighting circuits.

## Safety advice:

Not suitable for use with NON-dimmable LEDs fluorescent lamps and tubes, wire wound or toroidal transformers or electric motors. Do not overload. Product: TRIAC Leading Edge dim Technology2-way Push-On/Off, Rotary LED DimmerFrom 0 - 100W (max 10 LEDs)Without flickering with minimal dimming



## **Product Features:**

- Can be used to replace dimmers in existing front plates
- □ V-Com advanced dimming technology
- Soft-start function and intelligent overload protection
- Automatic configuration with manual adjustment options for minimum brightness and dimming mode to optimize the performance of a specific LED lighting load

**Safety standard:** BS EN 60669-2-1 / IEC669-2-1

**EAN-code:** 5021575001549 **Tariff code:** 85365007

Warranty: 10 years

