

3 VOLT CARBON MONOXIDE DETECTORS (CO-detector) XC-SERIE



XC70-NEFR-A

XC100-NEFR-A

XC100D-NEFR-A

XC-SERIE: 7- AND 10 YEAR CARBON MONOXIDE DETECTOR INCL. 3V BATTERY

Electrochemical detection; reliable Honeywell sensor technology
European production
Power: sealed long life 3V lithium battery
Operating temperature: -10 - + 45° C
Humidity: 25-95% relative humidity (non-condensing)
Maintenance-free operation, battery replacement unnecessary
Provided with test button, continuous self-test function every 60 minutes
Audible: 90 dB (1m) // by testing: ca. 75 dB
Pre-alarm function can be activated
Dimensions: 100 x 72 x 36 mm Weight: 133 gram Color: off-white
Degree of protection IP44 ➤ Suitable for bathroom conditions
Lifetime and warranty depending on model:
➤ Model XC70-NEFR-A: 7 years
➤ Model XC100-NEFR-A en XC100D-NEFR-A: 10 years
Alarm Scan App: Allows users to download [mostly the professional] data from the alarm to a smart device to directly investigate possible incidents.
Certification: BSI EN50291-1:2010 and BSI EN50291-2:2010 / A1 :2012
Easy installation
Packing: carton gift box with euroloch
User manual in packaging: Dutch and French, English and German on www.fito.nl
EAN-code Model XC70-NEFR-A: 5 027526 402069
EAN-code Model XC100-NEFR-A: 5 027526 402076
EAN-code Model XC100D-NEFR-A: 5 027526 402083
All Honeywell X-Series alarms can be wirelessly interconnected using the XW100 plug-in module. This means that if one X-Series Carbon Monoxide or smoke or heat alarm triggers an alarm, all interconnected units will give an audible alarm as well.
Note: in the event of an alarm there is no difference in sound between carbon monoxide, heat or smoke detection. In addition to a sound signal, the detecting detector also emits a red flashing light signal.